

~~41~~ Fig. 4 is a side view of a lead line for use with the tangle free fishing pole of Figs. 1-3.

Please substitute the following paragraph for the paragraph beginning on page 5, line 6:

A2 (Amended) Now, additionally referring to Fig. 3, captivating device 32 is a ferrule 32 having a tubular section 34, a shoulder section 36 and an axial hole 38 therethrough. The ends of elongated tube 30 are disposed near the openings of line guides 28 and captivating devices 32 are attached to elongated tube 30 by going through line guides 28. Tubular section 34 is sized to be detachably inserted into elongated tube 30. Tubular section 34 has raised annular rings 35 on the outer surface to retain elongated tube 30. Alternatively, tubular section 34 may retain elongated tube 30 using a crimp or an adhesive. Shoulder section 36 is circular in shape and is sized to not pass through the opening of line guide 28. Axial hole 38 is cylindrical and is substantially centered on the axis of captivating device 32. Fishing line 16 travels through a captivating device 32, elongated tube 30 and an other captivating device 32.

IN THE DRAWINGS

Please amend the drawings as shown in the Request for Approval of Drawing Changes attached herewith.

IN THE CLAIMS

Please cancel claim 2 and please substitute the following amended claims 1, 10 and 15 for original claims 1, 10 and 15:

- B1
A3 102
utsumo
1. (Amended) A tangle free fishing pole, comprising:
a fish pole having a plurality of fishing line guides thereon; and
a fishing line containment apparatus installed through at least two of said plurality of fishing line guides;